

USB 3.0 2.5" / 3.5" / SSD SATA HDD SmartDOCK

Model No: **VPP-89038P**



Product Overview:

ViPower VPP-89038P series is 2.5" and 3.5" SATA HDDs and SSD compatible docking station featured with the latest USB 3.0 SuperSpeed interface. This series allows for maximum data transfer rate of up to 5Gbps, which is ten times faster than conventional USB 2.0 devices while maintaining backward compatibility with USB 2.0 and 1.1 standards. Supporting with HDD hot-swap removable, installation is easy and quick and no screw is needed. Patented design with strong and reliable basement warrants reliable HDD operation.



Power/Read/Write
LED indicators



USB 3.0
connector x 1



2.5" and 3.5" SATA HDD
and SSD compatible



Power consumption less
than 1W in Standby Mode

Features:

- Support Hot-swap removable SATA I & SATA II HDDs
- Compatible with 2.5" and 3.5" SATA HDDs and SSD
- Support USB 3.0 SuperSpeed (5Gbps), USB 2.0 Hi-Speed (480Mbps), and USB 1.1 (1.5Mbps)
- LED Power/Read/Write indicators
- Power consumption under 1W in off mode and standby mode

Specifications:

Interface to PC	USB 3.0
HDD Supports	2.5" and 3.5" SATA HDDs and SSD
Material	Plastic
Indicator	LEDs for power and data access
Data Transfer Rate	5Gbps (USB 3.0 mode only)
Input Power	DC +12V/2A, 24W
Dimension	148.5mm(L) x 148.5mm(W) x 94.5mm(H)
Certification	FCC, CE

System Requirement:

- Any system with USB 3.0 (recommended) or 2.0 port
- Windows XP, Vista, and 7 operation system

Package Contents:

- External Docking Station (VPP-89038P)
- 2.5" HDD Bracket
- 3.5" HDD Clip x 2 (For Low-profile HDD)
- Wall-mount AC-DC Power adapter
- USB 3.0 cable

Power Supply:

- Universal auto-switching external power adapter
- Input: AC 100-240V, 50-60Hz
- Output: DC +12V/2A, 24W
- Certification: CE, GS, FCC, UL, CUL, TUV, CCC, C-Tick, PSE, KCC, SAA
- Overload Latch-Off protection during either specified power threshold requirements or short circuit condition

20100409